

-2-

AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions and listings of claims in the application.

1 1. (Canceled)

1 2. (Presently Amended) A side impact air bag curtain apparatus comprising:
2 an inflatable air bag adapted to be installed within a vehicle in a stowed condition
3 proximate a roof rail of a vehicle and when inflated expands from the stowed condition
4 to a deployed condition generally in front of an adjacent side of the vehicle;
5 the air bag including at least one movable air bag anchor at an end of the air bag;
6 and
7 a force-directing member or guide fixedly mounted at a determinable orientation
8 within the vehicle and adapted to slidably receive and support the movable air bag
9 anchor, wherein upon inflation of the air bag, the air bag moves to the deployed
10 condition causing the movable anchor to slide down the force-directing member so that
11 upon inflation of the air bag the movable anchor is self located in or near a center of the
12 force-directing member resisting any tendency of the curtain to move or be moved
13 upwardly;
14 wherein the force-directing member includes an bent element having a single
15 bend forming an apex, with the element mounted such that an apex of the element
16 tends to cause the movable air bag anchor to self-center.

1 3. (Withdrawn) The system as defined in Claim 6 wherein the force-directing
2 member includes a positive locking portion.

1 4. (Withdrawn) The system as defined in Claim 6 wherein the force-directing
2 member includes an apex directed away from the air bag.

Serial No. 10/021,470

-3-

1 5. (Withdrawn) The system as defined in Claim 6 wherein the force-directing
2 member includes a shaped channel in an adjacent vehicle pillar.

1 6. (Presently Amended) A side impact air bag curtain apparatus comprising:
2 an inflatable air bag adapted to be installed within a vehicle in a stowed condition
3 proximate a roof rail of a vehicle and when inflated expands from the stowed condition
4 to a deployed condition generally in front of an adjacent side of the vehicle;
5 the air bag including at least one movable air bag anchor at an end of the air bag;
6 and
7 a force-directing member or guide fixedly mounted to the vehicle adjacent one
8 side of the deployed air bag, and adapted to slidably receive and support the movable
9 air bag anchor, comprising an arcuate bar configured with an apex formed as a single
10 bend in the bar, facing the one side of the deployed air bag wherein upon inflation of the
11 air bag, the air bag moves to the deployed condition causing the movable anchor to
12 slide down the bar so that upon inflation of the air bag the movable anchor is self
13 located within the apex of the bar.

1 7. (Previously presented) The system as defined in Claim 6 wherein the bar includes
2 ends which respectively extend angularly away from the apex.

1 8. (Previously presented) The system as defined in Claim 6 wherein the bar includes a
2 first portion mounted vertically in the vehicle and a second portion which extends
3 angularly therefrom.

1 9. (Previously presented) The system as defined in Claim 6 wherein the bar includes a
2 first portion mounted horizontally in the vehicle and a second portion which extends
3 angularly therefrom and away from the one side of the air bag.

1 10. (Previously presented) The system as defined in Claim 6 wherein the bar includes a
2 first portion and a second portion which extend outwardly from the apex and wherein
3 the first and second portions are each skew mounted relative to the vehicle.

Serial No. 10/021,470

-4-

1 11. (Presently Amended) A side impact air bag curtain apparatus comprising:

2 an inflatable air bag adapted to be installed within a vehicle in a stowed condition
3 proximate a roof rail of a vehicle, the air bag having a determinable side-to-side width
4 when uninflated and when inflated expands from the stowed condition to a deployed
5 condition generally in front of an adjacent side of the vehicle, additionally when inflated
6 the width of the air bag is reduced in dimension;

7 the air bag including at least one movable air bag anchor at an end of the air bag;
8 and

9 a guide fixedly mounted to the vehicle, the guide defining an inflection point
10 configured as a single bend, the guide adapted to slidably receive and support the
11 movable anchor, wherein upon inflation of the air bag, the air bag moves to the
12 deployed condition causing the movable anchor to slide down the guide so that upon
13 inflation of the air bag the movable anchor is self located in or near the inflection point of
14 the guide thereby resisting any tendency of the curtain to move or be moved while the
15 curtain is inflated.

1 12. (Previously presented) The system as defined in Claim 2 wherein the element is
2 a rod.